

STERILLIGHT Air G1 30


AIR STERILIZATION

APPLICATION

Households, office spaces, healthcare and school facilities, retail establishments, hotels

BENEFITS

Air sterilization in the presence of people, quiet operation

GUARANTEE

24 months

AIR FLOW	Forced circulation	AIR PUMP VOLUME	30 m ³ / h
NOMINAL WATTAGE	40 W	NOMINAL VOLTAGE	230 V , 50 Hz
SOUND PRESSURE LEVEL - DEVICE	42 dB(A)	SOUND PRESSURE LEVEL - FAN	17,7 dB(A)
LIFESPAN - DEVICE (t_a = 25 °C, φ = 60 %)	60000 h	LIFESPAN - UV-C SOURCE	9000 h
UV-C RADIATION SOURCE	2 x 15 W (G13)	INGRESS PROTECTION RATING	IP20
DIMENSIONS (L x W x H)	749 x 220 x 91 mm	WEIGHT	5,5 kg
CONSTRUCTION MATERIAL	Extruded aluminum alloy	MOUNTING	Wall mounting
SURFACE TREATMENT	Powder coating RAL 9003		
OPTIONAL ACCESSORIES	Mobile floor stand, furniture stand, hanging accessories, timer		



OZONE FREE TECHNOLOGY

